

Bowlers Axis over 5.5 x 0 up

Starting Top 3.15 fingers 1.5" deep	Location	RG	Diff	MB
No Holes (2.5" Pin Distance)	n/a	2.466	0.053	0.012
W/Holes (Pin Up/CG Middle Span)	n/a	2.466	0.055	0.024
W/Holes + BH#1 P3-P4	3 over x 1.75 Down	2.461	0.064	0.028
W/Holes + BH#2 P1	5.5 over x 0	2.461	0.057	0.014
W/Holes + BH#3	7 over x 2 up	2.462	0.056	0.016
W/Holes + BH#4	9 over x 3 up	2.463	0.060	0.025
W/Holes + BH#5	0 over x 10 up	2.464	0.064	0.034
W/Holes + BH#6	-9 over x 3 up	2.463	0.060	0.025
W/Holes + BH#7	-7 over x 2 up	2.462	0.056	0.016
W/Holes + BH#8	-5.5 over x 0	2.461	0.057	0.014
W/Holes + BH#9	-3 over x 1.75 Down	2.461	0.064	0.028

Starting Top 3.15 fingers 1.5" deep	Location	RG	Diff	MB
No Holes	n/a	2.466	0.053	0.012
W/Holes (Pin Up/CG Middle Span)	n/a	2.466	0.055	0.024
W/Holes + BH#1 P3-P4	3 over x 1.75 Down	2.463	0.060	0.027
W/Holes + BH#2 P1	5.5 over x 0	2.463	0.056	0.019
W/Holes + BH#3	7 over x 2 up	2.464	0.056	0.020
W/Holes + BH#4	9 over x 3 up	2.464	0.060	0.025
W/Holes + BH#5	0 over x 10 up	2.465	0.058	0.030
W/Holes + BH#6	-9 over x 3 up	2.464	0.060	0.025
W/Holes + BH#7	-7 over x 2 up	2.464	0.056	0.020
W/Holes + BH#8	-5.5 over x 0	2.463	0.056	0.019
W/Holes + BH#9	-3 over x 1.75 Down	2.463	0.060	0.027

Starting Top 3.15 fingers 3.5" deep	Location	RG	Diff	MB
No Holes (2.5" Pin Distance)	n/a	2.466	0.053	0.012
W/Holes (Pin Up/CG Middle Span)	n/a	2.469	0.053	0.027
W/Holes + BH#1	3 over x 1.75 Down	2.464	0.062	0.031
W/Holes + BH#2	5.5 over x 0	2.464	0.055	0.017
W/Holes + BH#3	7 over x 2 up	2.465	0.054	0.019
W/Holes + BH#4	9 over x 3 up	2.466	0.058	0.027
W/Holes + BH#5	0 over x 10 up	2.468	0.061	0.035
W/Holes + BH#6	-9 over x 3 up	2.466	0.058	0.027
W/Holes + BH#7	-7 over x 2 up	2.465	0.054	0.019
W/Holes + BH#8	-5.5 over x 0	2.464	0.055	0.017
W/Holes + BH#9	-3 over x 1.75 Down	2.464	0.062	0.031

Starting Top 1.06 fingers 3.5" deep	Location	RG	Diff	MB
No Holes (2.5" Pin Distance)	n/a	2.465	0.054	0.012
W/Holes (Pin Up/CG Middle Span)	n/a	2.469	0.053	0.027
W/Holes + BH#1	3 over x 1.75 Down	2.465	0.062	0.031
W/Holes + BH#2	5.5 over x 0	2.465	0.055	0.017
W/Holes + BH#3	7 over x 2 up	2.466	0.054	0.019
W/Holes + BH#4	9 over x 3 up	2.466	0.058	0.027
W/Holes + BH#5	0 over x 10 up	2.468	0.061	0.035
W/Holes + BH#6	-9 over x 3 up	2.466	0.058	0.027
W/Holes + BH#7	-7 over x 2 up	2.466	0.054	0.019
W/Holes + BH#8	-5.5 over x 0	2.465	0.055	0.017
W/Holes + BH#9	-3 over x 1.75 Down	2.465	0.062	0.031

Starting Top 3.15 fingers 1.5" deep	Location	RG	Diff	MB
No Holes (2.5" Pin Distance)	n/a	2.466	0.053	0.012
W/Holes (Pin Up/CG Middle Span)	n/a	2.466	0.055	0.024
W/Holes + BH	8 over x 0	2.461	0.057	0.015
W/Holes + BH	10 over x 0	2.463	0.058	0.023
W/Holes + BH	8 over x 4.5 Down	2.468	0.051	0.024
W/Holes + BH	8 over x 3.375 Down	2.467	0.051	0.021
W/Holes + BH	8 over x 2.25 Down	2.465	0.053	0.018
W/Holes + BH	10 over x 4.5 Down	2.470	0.047	0.024
W/Holes + BH	10 over x 3.375 Down	2.469	0.048	0.022
W/Holes + BH	10 over x 2.25 Down	2.467	0.051	0.021

